

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 432 926 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
24.04.1996 Bulletin 1996/17

(51) Int. Cl.⁶: **B41F 17/02**, G07F 19/00,
B42D 9/04, G07F 7/10

(21) Application number: 90312758.7

(22) Date of filing: 23.11.1990

(54) **Apparatus for printing data in a book, a notebook, or the like**

Vorrichtung zum Datenaufdrucken in einem Buch, einem Notizbuch oder ähnlichem

Dispositif d'impression de données dans un livre, un agenda ou similaire

(84) Designated Contracting States:
DE FR GB

(30) Priority: 24.11.1989 JP 303212/89
07.12.1989 JP 316444/89
12.12.1989 JP 320653/89

(43) Date of publication of application:
19.06.1991 Bulletin 1991/25

(73) Proprietor: KABUSHIKI KAISHA TOSHIBA
Kawasaki-shi, Kanagawa-ken 210, Tokyo (JP)

(72) Inventor: Nukada, Hideki,
c/o Intellectual Property Division
Minato-ku, Tokyo 105 (JP)

(74) Representative: Freed, Arthur Woolf et al
MARKS & CLERK,
57-60 Lincoln's Inn Fields
London WC2A 3LS (GB)

(56) References cited:

GB-A- 2 104 493 US-A- 4 280 036
US-A- 4 772 896

- PATENT ABSTRACTS OF JAPAN vol. 13, no. 265 (M-839)(3613) 19 June 1989 & JP-A-1 064 879 (NEC CORP) 10 March 1989
- IBM TECHNICAL DISCLOSURE BULLETIN. vol. 27, no. 6, November 1984, NEW YORK US pages 3427 - 3428; T. HAMA AND K. TSUKAMOTO: 'Passbook-clamping mechanism for rotary feed drum'
- IBM TECHNICAL DISCLOSURE BULLETIN. vol. 30, no. 5, October 1987, NEW YORK US pages 4 - 6; 'Auto turn-page mechanism for passbook printer'

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

The present invention relates to an apparatus for printing data on any desired page of a book, a notebook, a bank book, or the like.

Generally, books are manufactured in the following steps. First, a plurality of sheets of paper of the same size is prepared. Then, different items of data are printed on each sheet. Next, the printed sheets are bound together, thus forming a book. Usually, once a book has been thus manufactured, a printing process is not performed several times to print different items of data on any specified page of the book. It is well expected that there will be necessary to print various items of data on any specified page of a book, a notebook, or the like, of in any specified region of a page. The following problems will arise in performing printing several times to print data items on a specified page of a book.

1) In a multilayer printing, e.g., a multicolor printing, a yellow image, a magenta image, and a cyan image must be sequentially printed on a desired page of a book. Unless the page is set at the same portion every time an image is printed, thereby printing the three images in complete alignment, the resultant color image or characters will not look as beautiful as is desired.

2) To print data on the whole area of a page of a book, the book must be fully opened. When the book is opened too much, the seamed portion of the pages may be damaged.

3) To print data in a specified region (e.g., a line or a box) on the desired page of a bank book, the page must be set at a correct position. Otherwise, the data will be printed outside the specified region, or partly within and partly without the region.

Accordingly, it is an object of this invention to provide an apparatus for printing data in a book, a notebook, or the like, which can securely print data at a specified position on any page of the book, the notebook or the like and which is free of the problems point out above.

Generally, it is necessary to reciprocate a print head several times over the same portion of a sheet of paper, in order to print data on that portion of the sheet repeatedly. Often the sheet is moved a little as the head moves in frictional contact with the sheet after different data has been printed on the sheet. Consequently, the newly printed data is not aligned with the previously printed data, causing a print drift and, inevitably, impairing the print quality. To prevent such a print drift, the sheet may be stretched and held tense and flat.

Patent Abstracts of Japan; vol. 13; No 265 (M-839) (3613) 19 June 1989 discloses apparatus for printing passbooks. This apparatus is intended to print data on any specified page of the passbook which consists of a plurality of pages fastened together at a seam. The apparatus has means for transporting the passbook to a predetermined position, while keeping a selected page of

the passbook opened and located substantially parallel to the other pages including the specified page on which data is to be printed. Means are provided for positioning and holding the specified page. Printing means prints data on the specified page.

US-A-4772896 discloses printing apparatus having clamping rollers and printing means which print desired data on one of the intermediate pages of a booklet. The printing is carried out using a thermal head while keeping end portions of a cover page and the intermediate page of the booklet clamped using the clamping rollers.

US-A-4280036 discloses printing apparatus having a page turning mechanism.

According to the present invention, there is provided an apparatus for printing data on any specified page of a book formed of a plurality of pages fastened together at a seam, said printing apparatus comprising: means for transporting the book to a predetermined position, while keeping a selected page of the book opened and located substantially parallel to the other pages including the specified page on which to print data; means for positioning and holding the specified page; and means for printing data on the specified page; characterized by further comprising: page-turning means for turning the specified page from the other pages of the book transported by the transporting means; and tension-applying means for pulling the selected page of the book, other than said specified page positioned and held by said positioning/holding means, so as to apply a tension on said specified page through the seam of the book.

The inventor of the present invention has paid attention to the fact that a plurality of pages of a book and the like are fastened together at the seam portion, and proposes an apparatus for tensing and flattening the page on which to print data (hereinafter called "print page"), without directly stretching the page. Specifically, in the present invention, the print page is not stretched. Rather, any one of the other pages is pulled while the print page is held at its fore-edge portion. The pull applied on the other page acts on the print page, too, through the seam of the book, since every pages are fastened together at the seam. Not only the page being pulled, but also the print page is rendered tense and flat. Hence, there will occur no print drift, no matter how many times data is printed on the same specified region of the print page. High-quality printed data, e.g., a color image without no color drift, can be obtained.

In order to directly stretch the print page tense and flat, the four corners of the page may be held and pulled outwards. This method cannot be used when data is to be printed on the entire print page, since the corners of the page are covered by the holders. To print data on the entire page, it is desirable to apply a tension on any page other than the print page. It is more desirable to apply a tension on the front or back cover of the book which is thicker than the pages and less liable to be damaged.

This invention can be more fully understood from the following detailed description when taken in conjunction with the accompanying drawings, in which:

Figs. 1 to 13 show a printing apparatus according to an embodiment of the present invention, in which:

Fig. 1 is a left-side view of the apparatus, illustrating the internal structure of the apparatus;

Fig. 2 is a right-side view of the apparatus, showing the internal structure thereof;

Fig. 3 is a plan view schematically showing the printing apparatus while a printing mechanism is removed;

Fig. 4 is a perspective view showing a platen roller and also the components associated with the platen;

Fig. 5 is a perspective view showing a chucking mechanism of the apparatus;

Fig. 6 is a side view illustrating the chucking mechanism in its opened state;

Fig. 7 is a side view showing the chucking mechanism in its closed state;

Figs. 8 to 13 are side views, explaining how the apparatus operates;

Fig. 14 is a perspective view showing a modified chuck sensor; and

Fig. 15 is a side view schematically showing a modified chucking mechanism.

An embodiment of the invention, which is an apparatus for printing data in a bank book, will be described with reference to the accompanying drawings.

As is shown in Figs. 1 to 3, the printing apparatus comprises a base 10, two parallel side walls 12 and 14, a front wall, and a rear wall. The side walls 12 and 14, the front wall and the rear wall are connected at their vertical sides, thus forming a housing. Arranged in this housing are: a book-guiding mechanism 16, a book-transporting mechanism 38, a page-turning mechanism 62, a page-holding mechanism 80 for holding the page of the book, a printing mechanism 96, and various drive mechanisms (later described) for driving the above-mentioned mechanisms. An inlet port 17 is made in the front wall, and an outlet port 18 is formed in the rear wall.

The guiding mechanism 16 comprises three lower guides 20a, 20b, and 20c, and two upper guides 22a and 22b. The lower guides 20a to 20c are arranged in end-to-end relation, between the inlet port 17 and the outlet port 18. Similarly, the upper guides 22a and 22b are arranged in end-to-end relation, and continuously extend from the inlet port 17 toward the outlet port 18. The upper guides are parallel to the lower guides, and a book-transporting path 23 is defined between the lower guides 20a to 20c, on the one hand, and the upper guides 22a and 22b, on the other. The path 23 has a height slightly greater than the thickness of a bank book 1. The inlet portion of the path 23 close to the inlet port 17 is made broader than the other portion of the path. Therefore, the bank book 1 can easily be inserted into the path 23 and

smoothly transported through the path 23 from the inlet port 17 to the outlet port 18.

The second lower guide 20b is arranged to be rotatable and moved between an upper position (Fig. 1) and a lower position (Fig. 10) by a lower guide drive mechanism 24. In the upper position, the guide 20b defines the path 23. The drive mechanism 24 has an arm 25 which is connected at one end to the second lower guide 20b and rotatably coupled at the other end to the side wall 12. The other end of the arm 25 is also connected to a plunger/solenoid unit 30 by a cam 26, a lever 27, and a connecting arm 28. When the unit 30 is turned on, the second lower guide 20b is rotated from the lower position to the upper position.

The second upper guide 22b arranged to be movable along the path 23 between a forward position (Fig. 1) and a rearward position (Fig. 9), and can be moved by an upper guide drive mechanism 29. When set in the forward position, the second upper guide 22b has its forward end located adjacent to the first upper guide 22a, and its rear end facing to the middle portion of the third lower guide 20c. When set in the rearward position, the second upper guide 22b has its forward end aligned with that of the third lower guide 20c, and its rear end located in the vicinity of the outlet port 18.

The upper guide drive mechanism 29 has a pair of sliders 31 (only one shown) and a pair of guide rods 32 slidably supporting the sliders 31. Both sliders 31 are fastened to the sides of the rear-end portion of the guide 22b, respectively. The guide rods 32 are attached to the side wall 12 or 14 and extend parallel to the book-transporting path 23. One of the sliders 31 is partly inserted in an elongated hole made in the distal end of an arm 33 which is rotatably attached to the side wall 12. The proximal end of the arm 33 is connected to a plunger/solenoid unit 37 by a cam 34, a lever 35 attached to the side wall 12, and a connecting arm 36. When the unit 37 is turned on, both sliders 31 are moved toward the inlet port 17, sliding on the guide rods 32, whereby the second upper guide 22b is moved to the forward position.

As is shown in Fig. 1, the bank book 1 is inserted into the path 23 through the inlet port 17, with its cover 1a opened and the seam 1b extending horizontally and perpendicular to the longitudinal axis of the path 23. Once in the path 23, the book 1 is transported toward the outlet port 18 by means of the book-transporting mechanism 38.

As is illustrated in Figs. 1 and 2, the book-transporting mechanism 38 comprises three upper rollers 40a, 40b and 40c, and three lower rollers 41a, 41b and 41c - all arranged parallel to each other and along the book-transporting path 23. The upper rollers 40a, 40b and 40c are set in rolling contact with the lower rollers 41a, 41b and 41c, respectively, and apply a predetermined pressure thereto. The rollers 40a and 40b are spaced apart for a distance which is longer than the width of the cover 1a and shorter than the width of the book 1 opened. The rollers 40b and 40c are spaced apart for a distance which is shorter than the width of the cover 1a. The rollers of

the mechanism 38 are rotatably mounted on axles extending between the side walls 12 and 14. All these rollers are duplicated.

As is evident from Figs. 3 and 8, the second upper roller 40b consists of two rollers which are rotatably mounted on a shaft 42 extending horizontally and perpendicular to the longitudinal axis of the book-transporting path 23. The shaft 42 is rotatably supported, at both ends, by support arms 43 which in turn are rotatably supported, at one end, by an axle 44 extending between the side walls 12 and 14. Hence, as the support arms 43 rotate up and down, the rollers 40b are moved onto the second lower rollers 41b and away therefrom. One of the support arms 43 is connected by a tension spring 45 to a pressure-adjusting mechanism 46.

As is shown in Fig. 8, the pressure-adjusting mechanism 46 comprises a lever 47, an idler roller 48, an electric motor 49, and an eccentric cam 50. The substantially intermediate portion of the lever 47 is rotatably supported by the side wall 12. The idler roller 48 is rotatably mounted on one end of the lever 47. The tension spring 45 is connected to the other end of the lever 47. The motor 49 is fastened to the side wall 12. The eccentric cam 50 is fixed to the drive shaft 49a of the electric motor 49 and contacts the idler roller 48. As long as the cam 50 takes the position shown in Fig. 8, the lever 47 pulls the spring 45, thus biasing the support arms 43 to rotate counter-clockwise around the axle 44. In this condition, the rollers 40b are pressed onto the second lower rollers 41b, applying a predetermined pressure to the rollers 41b. When the motor 49 rotates the eccentric cam 50, the lever 47 is rotated clockwise, allowing the spring 45 to contract, which decreases the pressure the roller 40b applies to the roller 41b.

As is clearly illustrated in Fig. 2, the book-transporting mechanism 38 further comprises an electric motor 52 fixed to the side wall 14. A drive pulley 52a is secured to the drive shaft of the motor 52. Three pulleys 51a, 51b and 51c are fixedly mounted on the shafts of the lower rollers 41a, 41b and 41c, respectively. An endless belt 53 is wrapped around the drive pulley 52a, the second pulley 51b and the third pulley 51c. An endless belt 54 is wound around the first pulley 51a and the second pulley 51b. When the motor 52 is turned on, the pulley 52a is rotated, whereby the lower rollers 41a, 41b and 41c are rotated in the same direction. These rollers 41a, 41b and 41c have the same diameters, and are thus rotated at the same speed. Since the upper rollers 40a, 40b and 40c are in rolling contact with the lower rollers 41a, 41b and 41c, respectively, while applying the predetermined pressure thereto, they are also rotated as long as the drive pulley 52a is rotating. Hence, no drive means are required to rotate the upper rollers 40a to 40c. As the upper rollers 40a to 40c and the lower rollers 41a to 41c are thus rotated, the bank book 1 is transported forward through the path 23, while being pinched between the rollers of each pair.

As is shown in Figs. 1 to 4, a platen roller 56 is located above the upper guides 22a and 22b. The roller

56 is used to support any page of the book 1 so that data is printed on the page. This roller 56 is fixedly mounted on a platen shaft 57 which extends horizontally and at right angles to the path 23, and is rotatably supported at both ends by the side walls 12 and 14. Part of the outer circumference of the platen roller 56 is cut out to form a flat surface 56a which extends parallel to the axis of the platen 56. The roller 56 is rotated by a platen drive mechanism 58.

The platen drive mechanism 58 comprises an electric motor 59, a first pulley 60a, a second pulley 60b, and a third pulley 60c. The motor 59 is fastened to the side wall 14. The first pulley 60a is rotatably attached to the side wall 14. The second pulley 60b has a smaller diameter than the first pulley 60a and is integrally formed therewith. The third pulley 60c is fixedly mounted on the platen shaft 57. A drive pulley 59a is fixed on the drive shaft of the electric motor 59. An endless belt 61a is wound around the drive pulley 59a and the first pulley 60a. An endless belt 61b is wound around the second pulley 60b and the third pulley 60c.

The page-turning mechanism 62 comprises a pair of page-turning rollers 63. These rollers 63 are located near the platen roller 56 and above the second upper guide 22b. Both rollers 63 are fixed on a shaft 64 which extends horizontally and parallel to the platen shaft 57. The shaft 64 is rotatably supported, at both ends, by a roller holder 66. The holder 66 is rotatably supported by the platen shaft 57 and can, therefore, rotate independently of the platen roller 56 and holds the shaft 64 of the page-turning rollers 63 always at a predetermined distance from the platen shaft 57. The holder 66 has a guide surface 66a which extends along the tangent to the roller 56 from a position near the circumference of the roller 56 to a position near that of the page-turning rollers 63. The circumference of either roller 63 is a layer of material having a great friction coefficient, such as rubber.

The page-turning mechanism 62 further comprises an electric motor 67, a pulley 68, a drive roller 69, a first driven roller 70, an a second driven roller 71. The motor 67 is fastened to the side wall 14. The pulley 68 is integrally formed with the drive roller 69 and has a diameter smaller than that of the roller 69. The drive roller 69 is rotatably connected to the side wall 14. The first driven roller 70 is rotatably mounted on the platen shaft 57. The second driven roller 71 is fixed to the shaft 64. A drive pulley 67a is fastened to the drive shaft of the motor 67. An endless belt 72 is wrapped around the drive pulley 67a and the pulley 68. As is best shown in Fig. 3, the first driven roller 70 is set in rolling contact with the drive roller 69 and the second driven roller 71. Hence, when the motor 67 is turned on, its driving force is transmitted to the page-turning rollers 63 by the belt 72, the pulley 68, and the rollers 69, 70 and 71.

As is shown in Fig. 1, the page-turning mechanism 62 has a holder-driving mechanism 73 for rotating the roller holder 66 to move the page-turning rollers 63 to a desired position, for example, a position where they contact that page of the book 1 on which to print data. The

mechanism 73 comprises an electric motor 74 and an arm 75. The motor 74 is fixed to the side wall 12. One end of the arm 75 is rotatably mounted on an axle fastened to the side wall 12. The arm 75 has an elongated hole in its distal portion. A pin protruding from the roller holder 66 is inserted in this elongated hole. A pulley 76 is fixed to the arm 75, coaxial with the axle of thereof. A drive pulley 74a is connected to the drive shaft of the motor 74. An endless belt 77 is wrapped around the drive pulley 74a and the pulley 76. Hence, the driving force of the motor 74 is transmitted to the arm 75 by the pulleys 74a and 76 and the endless belt 77, whereby the roller holder 66 is rotated to move the page-turning rollers 63 to the desired position.

As is illustrated in Fig. 3, a sensor 78 is located above the second upper guide 22b and between the second upper rollers 40b and the page-turning rollers 63. The sensor 78 is used to detect how the pages of the bank book 1 are being turned. The sensor 78 has a light-emitting element 78a and a light-receiving element 78b. The element 78a is secured to the side wall 12, for emitting a light beam. The element 78b is secured to the side wall 14 and opposes the light-emitting element 78a, for receiving the light beam emitted therefrom. Both elements 78a and 78b are inclined at a predetermined angle α to the seam 1b of the bank book 1, so that the light beam propagates from the element 78a to 78b in a line inclined at the same angle to the seam 1b of the book 1.

When the page-turning mechanism 62 turns any page of the bank book 1, the page is bent or waved. The crest of the waved page interrupts the light beam emitted from the light-emitting element 78a. As a result of this, the sensor 78 detects that the page is turned correctly.

The printing apparatus further comprises a chucking mechanism 80 (or a page-holding mechanism) which cooperates with the platen roller 56 to position and holds the print page.

As is shown in Fig. 1, Figs. 3 to 5, and Fig. 7, the chucking mechanism 80 comprises a pair of chucking members 82 and a drive unit 83. The chucking members 82 are attached to the ends of the platen roller 56, respectively. The drive unit 83 is provided for driving these members 82. Either chucking member 82 has a semicircular support plate 84 and a chucking arm 85. The support plate 84 is mounted on the end face of the platen roller 56 and is coaxial therewith. The chucking arm 85 protrudes from the circumference of the support plate 84 and extends along the circumference of the roller 56 and parallel to the axis of the roller 56. The semicircular support plate 84 has a circular hole 84a and an elongated hole 84b, which are located diametrically opposite to each other. The elongated hole 84b extends in a circle concentric to the circular hole 84a. The support plate 84 is connected to the end face of the platen roller 56 by two screws 86a and 86b. The screw 86a extends through a washer and the hole 84a and is set in screw engagement with the roller 56. Similarly, the screw 86b extends through a washer and the hole 84b and is set in screw engagement with the roller 56. Both screws 86a

and 86b are loosely screwed into the platen roller 56, and the support plate 84 can rotate about the screw 86a until either end of the elongated hole 84b abuts on the screw 86b. A rubber pad 85a, which has a great friction coefficient, is secured to that side of the chucking arm 85 which opposes the platen roller 56.

A connector 87 is formed on that end of the support plate 84 which is close to the elongated hole 84b, and a connector 88 protrudes from the end of the platen roller 56. A tension spring 89 is stretched between these connectors 87 and 88, biasing the support plate 84 clockwise around the screw 86a. Hence, the chucking arm 85 is pressed onto the circumference of the platen roller 56. An engagement portion 90, which can engage with the drive unit 83, is formed on that end of the support plate 84 which is close to the circular hole 84a.

The drive unit 83 has a pair of claws 91 which can abut against the engagement portions 90 of the chucking members 82. These claws 91 are fastened to a shaft 92. The shaft 92 is rotatably supported at both ends by the side walls 12 and 14 and extends parallel to the platen roller 56. One of the first claws 91 is connected by a connecting rod 94 to a plunger/solenoid unit 93 which is secured to the side wall 12. Usually, the claws 91 are spaced at some distance from the engagement portions 90 of the chucking members 82. Thus, the chucking member 82 is held at the chucking position shown in Fig. 7 due to the force of the spring 89. When the plunger/solenoid unit 93 is turned on in order to print data on any page of the bank book 1, the connecting rod 94 is moved such that the claws 91 are rotated in the direction of arrow A (Fig. 5), along with the shaft 92. Each claw 91 abuts on the engagement portion 90 of the corresponding chucking member 82. Each chucking member 82 is therefore rotated to the waiting position (Fig. 6) against the force of the spring 89. While set in the waiting position, the pad 85a of the chucking arm 85 remains away from the circumference of the platen roller 56. When the print page of the bank book 1 is inserted into the gap between the platen roller 56 and the arm 85, the plunger/solenoid unit 93 is turned off. Either chucking member 82 is rotated from the waiting position to the chucking position, whereby the rubber pad 85a is pressed onto the circumference of the platen roller 56. As a result of this, the print page is clamped between the platen roller 56 and both chucking arms 85 and, thus, held at a predetermined position.

As is illustrated in Figs. 5 to 7, a detection rod 95a extends from one of the chucking members 82 in the radial direction thereof. The distal end of this rod 95a is placed in the recess of a chuck sensor 95b which is fastened to the side wall 14. The sensor 95b has a light-emitting element and a light-receiving element which oppose each other across the recess. When the rod 95a slightly rotates in interlock with the rotation of the chucking member 82, the sensor 95b detects a minute movement of the rod 95a and outputs an electric signal. This signal is supplied to a control device (not shown).

The initial value for the output signal of the chuck sensor 95b is obtained in the following manner. First, both chucking members 82 are located at the chucking position, and nothing is inserted in the gap between the platen roller 56 and both chucking arms 85. In this condition, the sensor 95b detects the position of the rod 95a and generates an electric signal. The level of this signal is used as the initial value of the output signal of the chuck sensor 95b.

The initial value for the output signal of the chuck sensor 95b, thus obtained, is stored into a memory incorporated in the control device. When the print page of the book 1 is held between the platen roller 56 and the chucking arms 85, the arms 85 are slightly spaced apart from the circumference of the roller 56 by the distance equal to the thickness of the print page. By detecting this distance, it is possible to determine that the print page is correctly held between the platen roller 56 and the chucking arms 85 or not. More precisely, when the page is inserted into between the roller 56 and the arms 85, the chucking member 82 rotates by a very small angle. Simultaneously, the detection rod 95a moves within the recess of the chuck sensor 95b for a short distance proportional to the angle of rotation of the chucking member 82. This motion of the rod 95a is detected by the chuck sensor 95b, which outputs a signal to the control device. Since the rod 95a protrudes rather long from the chucking member 82, the minute rotation of the member 82 is translated into the prominent motion of the rod 95a which the chuck sensor 95b can detect with high reliability.

As is evident from Figs. 1 and 2, the printing mechanism 96 is arranged above the platen roller 56. The printing mechanism 96 comprises a head unit 97 and a ribbon unit 98. The head unit 97 has a support arm 97a and a print head 97b. The arm 97a is rotatably connected at proximal end to the side wall 12. The print head 97b is fastened to the distal end of the arm 97a and located above the platen roller 56. The ribbon unit 98 has a pair of reels 98a and a length of ink ribbon 98b. The reels 98a are rotatably supported between the side walls 12 and 14. The ink ribbon 98b is fed from the first reel 98a, guided through the gap between the roller 56 and the print head 97b, and taken up around the second reel 98a. The print head 97b is a thermal head, and applies heat to the ink ribbon 98b, thereby to transfer the ink from the ribbon 98b onto the print page of the book 1. The ink ribbon 98b has a yellow region, a magenta region, and a cyan region, so that the printing apparatus can print not only characters but also color images in the book 1.

The support arm 97a is connected to a plunger/solenoid unit 99 by means of a connecting rod 100. The plunger/solenoid unit 99 is secured to the side wall 14. Usually, the print head 97b is spaced apart from the platen roller 56. When the unit 99 is turned on, the arm 97a is rotated toward the platen roller 56 until the print head 97b is brought into contact with the platen roller 56.

The operation of the printing apparatus, described above, will now be explained.

First, the book 1, with its cover 1a opened, is inserted into the book-transporting path 23 through the inlet port 17 as is illustrated in Fig. 1. At this time, the second lower guide 20b has been moved to its upper position by the lower guide drive mechanism 24, and the second upper guide 22b has been moved to its front position by the upper guide drive mechanism 29. The fore-edge portion of the cover 1a is held between the first upper rollers 40a and the first lower rollers 41a. The motor 52 of the book-transporting mechanism 38 is turned, thus rotating the lower rollers 41a, 41b and 41c. The first lower rollers 41a and the first upper rollers 40a transport the book 1 toward the outlet port 18. The fore-edge portion of the cover 1a is pinched between the second upper rollers 40b and the second lower rollers 41b before the fore edges of the other pages pass the rollers 40a and 41a. Therefore, the book 1 is continuously transported toward the outlet port 18.

As is shown in Fig. 8, the lever 47 of the pressure-adjusting mechanism 46 is at such a position that the second upper rollers 40b contact the book 1, applying the same pressure as any other book-feeding roller. At the time the seam 1b of the book 1 reaches a position near the second rollers 40b and 41b, the motor 52 is turned off, whereby the book 1 is stopped.

Then, the page-turning mechanism 62 is actuated to turn the pages of the book 1. As is shown in Fig. 9, the upper guide drive mechanism 29 moves the second upper guide 22b to its rear position, thus exposing the left pages of the book 1 to the page-turning mechanism 62. The motor 74 of the mechanism 62 is turned on, rotating the roller holder 66 until the page-turning rollers 63 contacts the upper-most left page of the book 1, i.e., the print page 1c. The rollers 63 cooperate with the second lower guide 20b, applying a sufficient pressure on the left pages of the book 1. In this condition, the motor 67 of the page-turning mechanism 62 is turned on, thereby rotating the rollers 63 in the direction of arrow B (Fig. 9). Thus rotated, the rollers 63 turn the print page 1c. Meanwhile, the pressure-adjusting mechanism 46 keeps the second upper rollers 40b in contact with the cover 1a of the book 1 at sufficient pressure. Hence, the rear-edge portion of the cover 1a is held between the rollers 40b and 41b, and the fore-edge portion of the cover 1a is held between the rollers 40c and 41c. The print page 1c can therefore be turned reliably.

At the time the rollers 63 start turning the print page 1c, the lower guide drive mechanism 24 rotates the second lower guide 20b to its lower position as is illustrated in Fig. 10. The left pages other than the first left page are thus prevented from being turned. As the rollers 63 is further rotated, the print page 1c is bent as is shown in Fig. 9. When the crest 1d of the bent portion of the print page 1c reaches to a predetermined level, the page 1c straightens itself due to its elasticity, and place itself upon the guide surface 66a of the roller holder 66 as is illustrated in Fig. 10. The moment the crest 1d reaches the predetermined level, it interrupts the light beam emitted from the light-emitting element 78a of the sensor 78. As

a result of this, the sensor 78 detects that the print page 1c has been turned correctly, and outputs a signal. This signal is supplied to the control device. Upon receipt of the signal, the control device turns off the motor 67 of the page-turning mechanism 62, thereby stopping the page-turning rollers 63.

Then, as is shown in Fig. 10, the book-transporting mechanism 38 rotates the lower rollers 41a, 41b and 41c in the reverse direction, that is, in the direction of arrow C a predetermined number of times. The lower rollers 41b and 41c and the upper rollers 40b and 40c transport the book 1 rearward, that is, toward the inlet port 17. At the same time, the drive unit 83 of the chucking mechanism 80 is actuated, rotating both of chucking members 82 to their waiting positions. The chucking arms 85 are thereby moved away from the circumference of the platen roller 56. In the meantime, the fore-edge portion of the print page 1c is guided upwards by the guide surface of the roller holder 66 and reaching the circumference of the platen roller 56. Both sides of the fore-edge portion of the page 1c are inserted into the gaps between the platen roller 56 and the chucking arms 85.

When the supply of power to the drive unit 83 of the chucking mechanism 80 is stopped in this condition, either chucking member 82 is rotated to its shucking position as is shown in Fig. 11 by the spring 89 until the chucking arm 85 presses the fore-edge portion of the print page 1c onto the circumference of the platen roller 56. Hence, the print page 1c of the book 1 is held at the predetermined position. Since the second lower guide 20b is at its lower position at this time, the left page of the book 1 hangs downwards. Meanwhile, the moment the chucking mechanism 80 starts performing its function, the control device compares the initial output value of the chuck sensor 95b with the value of the output signal actually output therefrom. If the values compared are equal, the control device determines that the print page 1c is not chucked due to its warping or its jamming condition. In this case, the control device prevents the printing mechanism 96 from initiating its function, and turns on the drive unit 83 again or outputs a signal indicative of a trouble in the printing apparatus. On the other hand, if the values compared are different, the control device determines that the print page 1c is chucked correctly, and then causes the following printing operation to print data on the print page 1c. In the case where the value of the signal output from the chuck sensor 95b is much greater or much less than the initial value, the control device determines that two or more pages have been clamped between the platen roller 56 and either chucking arm 85, and performs a different control.

Next, as is shown in Fig. 12, the driving mechanism 73 rotates the page-turning rollers 63, together with the roller holder 66, to the positions near the first upper guide 22a. The platen drive mechanism 58 rotates the platen roller 56 in the direction of arrow D for a predetermined angle, while the print page 1c is kept held on the platen roller 56. Simultaneously, the motor 52 of the book-transporting mechanism 38 is turned on. As a result of this,

the lower rollers 41a, 41b, and 41c are rotated in the direction of arrow E, thereby applying a tension on the cover 1a of the book 1. The tension is transmitted via the seam 1b to the print page 1c. Hence, the print page 1c is stretched tense and flat. At the same time the rollers 41a to 41c start rotating, the motor 49 of the pressure-adjusting mechanism 46 is turned on, whereby the eccentric cam 50 is rotated not more than 180 degrees in the direction of arrow F. Then, the idler roller 48 is rotated, thus rotating the lever 47 in the direction of arrow G. The tension spring 45 is therefore compressed, whereby the bias applied on the second upper rollers 40b decreases, and the pressure the rollers 40b exert on the second lower rollers 41b decreases proportionally. The rollers 40b therefore slips on the cover 1a of the book 1, not transporting the book 1 forward but applying an appropriate tension on the print page 1c. As a result, no excessive tension is applied to the print page 1c, thus preventing damages thereto.

As may be understood from the preceding paragraph, the second upper rollers 40b, the second lower rollers 41b, the pressure-adjusting mechanism 46, and the book-transporting mechanism 38 constitute a tension-applying mechanism for applying an appropriate tension to the print page 1c. Both the pressure the rollers 40b apply on the rollers 41b and the tension applied on the print page 1c can be controlled by adjusting the angle through which to rotate the eccentric cam 50.

Then, the plunger/solenoid unit 99 of the printing mechanism 96 is actuated, rotating the print head 97b until the head 97b presses the ink ribbon 98b onto the print page 1c which is held tense and flat and contact the circumference of the platen roller 56. In this condition, data is printed on the print page 1c while tension is applied to the print page 1c in the above-mentioned manner.

Specifically, as is evident from Fig. 13, the drive mechanism 58 rotates the platen roller 56 in the direction of arrow D by a predetermined angle, whereby the print page 1c is fed in the same direction. At the same time, the second reel 98a of the ribbon unit 98 is rotated, feeding the ink ribbon 98b in the direction of arrow H for a predetermined distance. In the meantime, the print head 97b transfers the ink from the ribbon 98b onto the print page 1c, thus printing data (e.g., characters or images, or both) on the page 1c. To accomplish multicolor printing, the steps shown in Figs. 12 and 13 are repeated three times, for printing a yellow image, a magenta image, and a cyan image in the same region of the print page 1c.

In the case where data is printed on almost the entire print page 1c, the page 1c is wrapped around the platen roller 56 at the end of the printing, and the book 1 takes the specific position illustrated in Fig. 13. Namely, the seam 1b of the book 1 is set in contact with the flat surface 56a of the platen roller 56, and the cover 1a opposes the left pages, defining an acute angle θ together with the left pages.

Upon completion of the printing, the control device controls the various drive mechanisms and drive units, thereby setting the movable components into the condition illustrated in Fig. 8. Then, the book-transporting mechanism 38 is driven, whereby the book 1 is transported through the path 23 and finally ejected through the outlet port 18 from the printing apparatus.

In order to print data on the next page of the book 1, the second lower guide 20b is rotated upwards from the position shown in Fig. 10, and the page-turning rollers 63 are moved upwards, away from the left pages of the book 1. Next, the book-transporting mechanism 38 is actuated, transporting the book 1 toward the inlet port 17. The rollers 63 prevent the print page 1c, which is now located above the guide surface 66a of either roller 63, from being moving further. The print page 1c is therefore turned back to the right and gradually opened as the book 1 is moved toward the inlet port 17. After the print page 1c is opened completely, the book-transporting mechanism 38 starts transporting the book 1 toward the outlet port 18, thereby setting the condition shown in Fig. 8. Hence, the page-turning mechanism 62 can turn the page next to the print page 1c, and the printing mechanism 96 can print data on the next page.

As has been described, during the printing operation, tension is applied on the cover 1a of the book 1 in the transporting direction of the book, so that the cover 1a and the print page 1c are stretched to locate on a common plane, as shown in Figs. 11 and 12. After data has been printed on the page 1c, and the print page 1c is turned, thus opening the next page so that data may be printed on the next page, a tension can be applied on the cover 1a or the print page 1c, or both. In whichever way the tension is applied, it is applied on the next page, too. The next page, or the new print page, is thereby made tense and flat, minimizing the print drift and achieving high-quality printing, no matter whether the data is characters or images. Since any print page is rendered tense and flat and is also correctly positioned, data can be printed at any specified portion of the page (e.g., a frame or lines, already printed on the page).

In the embodiment described above, the rollers 40b and 41b applies a tension in the direction at right angles to the seam 1b of the book 1. Nevertheless, the tension can be applied to the print page 1c in whichever direction by any means other than the rollers 40b and 41b. Moreover, the pressure-adjusting mechanism 46 can be replaced by any known mechanism which performs the same function.

As has been described, the pressure-adjusting mechanism 46 adjusts the pressure the roller 40b applies to the roller 41b, while rotating the rollers 40b and 41b at the same speed, in order to control the tension applied on the print page 1c. Without the mechanism 46, said pressure would remain unchanged, and it would be necessary to vary the speed of the roller 40b in order to control the tension applied on the page 1c. Were the speed of the roller 40b varied, the roller 40b should necessarily be rotated in reverse direction when the page 1c

is wrapped around the platen roller 56 to some extent. Obviously, it is difficult to rotate the roller 40b in the reverse direction at an appropriate time. If the reverse rotation of the roller 40b is not started timely, which may happen quite likely, the print page 1c will be warped, or an excessive tension will be applied on the seam 1b.

When the mechanism 46 reduces the pressure which the roller 40b applies to the roller 41b, the cover 1a can move backward through the gap between the rollers 40b and 41b even if the tension on the print page 1c changes as the print page 1c is gradually wrapped around the platen roller 56. Hence, the tension on the page 1c is automatically adjusted, and the page 1c remains tense and flat. Conversely, when the mechanism 46 increases the pressure the roller 40b applies to the roller 41b, these rollers 40b and 41b exerts a force great enough to transport the book 1 toward the outlet port 18. That is, by adjusting the contact pressure between the rollers 40b and 41b in accordance with the required function, these rollers 40b and 41b perform various functions with respect to the book. Hence, there is no need to use a drive means exclusively for transporting the book 1 toward the outlet port 18, which helps to simplify the internal structure of the printing apparatus and also to reduce the size of the apparatus.

In view of the two preceding paragraphs, the pressure-adjusting mechanism 46 is one of the characterizing features of the printing apparatus.

As has been pointed out, the second lower roller 41b can be stopped and rotated in the reverse direction by the motor 52 of the book-transporting mechanism 38. When the roller 41b is rotated in reverse direction, the book 1 is transported to the platen roller 56, whereby data can be printed on the print page 1c of the book 1. When the roller 41b is stopped, it holds the book 1 in place. As the second lower roller 41b moves the book 1 backward at a proper timing and stops the same at an appropriate timing, the page-turning operation can be smoothly performed.

As is illustrated in Figs. 10 to 13, the second lower guide 20b of the book-guiding mechanism 16 can be set at its lower position while data is being printed on the print page 1c. When the guide 20b is rotated downward, the left pages of the book 1, including the back cover, hang downwards by their own weights. Hence, the left pages are never be clamped between the guide 20b and the page-turning rollers 63. Were the left pages be clamped between the guide 20b and the rollers 63, they would be wrapped around the rollers 63 and curved. The back cover, in particular, which is thicker than the other pages in most cases, would be curved permanently, inevitably shortening the lifetime of the book 1. In order to make the left pages hang downwards, the second lower guide 20b can be moved toward the outlet port 18 in the same way as the second upper guide 22b.

Since the platen roller 56 has a flat surface 56a, the cover 1a is not perfectly face to the pages other than the print page 1c, as is shown in Fig. 13, even when the print page 1c is completely wrapped around the platen roller

56. Rather, the cover 1a is inclined at an angle θ to the other pages. If the roller 56 had not the flat surface 56a, the book 1 should be bent double at the seam 1b, with the cover 1a laid upon the other pages not printed yet, inevitably weakening the seam 1b and shortening the lifetime of the book 1.

In other words, due to the flat surface 56a of the platen roller 56, the book 1 can last long. The angle θ can be changed to a desired one by replacing the roller 56 with one having a cross section of a different shape.

As is shown in Figs. 12 and 13, the page-turning rollers 63 are moved to a position near the first upper guide 22a. This also serves to prevent weakening the seam 1b and shortening the lifetime of the book 1.

Since the roller holder 66 connects the page-turning rollers 63 to the platen roller 56, the distance between the roller 56 and the rollers 63 remains unchanged. Hence, the print page 1c is correctly positioned with respect to the platen roller 56 when the second lower roller 41b is rotated by the predetermined angle, no matter which of the page-turning rollers 63 has turned the print page 1c.

Moreover, since the guide surface 66a of the holder 66 is located between the platen roller 56 and the page-turning rollers 63, it smoothly guides the print page 1c to the platen roller 56. It is most desirable that the guide surface 66a extend along the tangent to both the platen roller 56 and either page-turning roller 63. However, the guide surface 66a can be curved. The guide surface 66a also serves to guide the print page 1c smoothly to the chucking arms 85.

Further, the guide surface 66a contacts the whole print page 1c as is illustrated in Fig. 10. Hence, the surface 66a supports the page 1c until the page 1c is wrapped around the platen roller 56. The force applied to the page 1c does not concentrate on the fore-edge portion of the page 1c to move this portion upwards from the circumference of the platen roller 56.

In the chucking mechanism 80, either chucking member 82 is located such that the platen shaft 57 is positioned between the connector 88 and the chucking arm 85 as is illustrated in Fig. 7. Therefore, the force which moves the arm 85 toward the circumference of the platen roller 56 to press the page 1c on the roller 56 has a vector component J which extends opposite to the direction K in which the print page 1c is transported.

As has been described, a tension is applied on the page 1c, which acts in the direction opposite to the direction K, in order to make the page 1c tense and flat before data is printed on the page 1c. Therefore, either chucking arm 85 must exert a great force to the print page 1c to hold the page 1c on the circumference of the platen roller 56. The arm 85 can readily acquire such a great force in the following manner. When the tension is applied on the print page 1c in the direction opposite to the direction K, a great friction is generated between the page 1c and the rubber pad 85a. This friction results in a rotation moment M in the chucking arm 85, which rotates the arm 85 around the screw 86a. Since the moment M has a

vector component acting in the same direction the tension acts on the page 1c, that is, in the direction opposite to the direction K. As a result, the vector component acts on either chucking arm 85 such that the arm 85 presses the print page 1c onto the circumference of the platen roller 56, whereby the page 1c is firmly held on the circumference of the roller 56.

The greater the tension applied on the print page 1c, the greater the rotation moment M of either chucking arm 85. The greater the moment M, the more firmly the chucking arm 85 holds the print page 1c on the circumference of the platen roller 56. Even if the pull acting on the page 1c increases when, for example, the print head 97b slides on the page 1c, the page 1c does not slip out from between the chucking arm 85 and the circumference of the roller 56, thus ensuring high-quality printing. Since the page 1c remains held on the circumference of the platen roller 56 throughout the printing process, the data is never be printed on the circumference of the platen roller 56.

As has been described, the chucking mechanism 80 has the detecting rod 95a and the chuck sensor 95b, and can reliably detect that the print page 1c is chucked firmly on the circumference of the platen roller 56. Thus, when the page 1c is not clamped between the platen roller 56 and either chucking arm 85 due to a trouble such as jamming or warping of the page 1c, the chuck sensor 95b can detect this trouble from the motion of the rod 95a, no matter how slight this motion is. In this case, the following printing operation is not performed, and the ink ribbon 98b is never directly wound around the platen roller 56.

The chuck sensor 95b can be a pressure sensor 102 which can contact with the circumference of the platen roller 56, as is illustrated in Fig. 14.

As has been described, the printing apparatus has the sensor 78 which detects how the pages of the book 1 are being turned. This is an optical sensor or an so-called "non-contact sensor," and need not contact the pages. As is known in the art, a non-contact sensor operates more accurately than a contact sensor such as a micro switch. The sensor 78 can, therefore, detect how the pages are turned, even if the pages of the book 1 are extremely soft and flexible.

If the sensor 78 were a micro switch, it could not be actuated by the crest 1d of the bent portion of the print page 1c, which rises gradually as the page-turning rollers 63 are rotated. Thus, the sensor 78 could not detect that the page 1c is bent, inevitably failing to determine how the page 1c is turned.

Further, since the light-emitting element 78a and light-receiving element 78b of the sensor 78 are inclined at the predetermined angle α to the seam 1b of the book 1, they can be easily arranged outside the book-transporting-path 23 as is shown in Fig. 3. Thus, they do not hinder the transportation of the book 1 or the movement of the book 1 during the printing process. Moreover, since the elements 78a and 78b are inclined at the predetermined angle α to the seam 1b of the book 1, the

passage of the light beam emitted from the element 78a to the element 78b is $1/\sin\alpha$ times longer than in the case the elements 78a and 78b are aligned at right angles to the book-transporting path 23. This is desirable when one or more pages of the book 1 are transparent or semi-transparent, or have a transparent or semi-transparent portion. The longer the path a light beam passes through a transparent or semi-transparent body, the more its intensity is attenuated. The more the intensity of the beam is attenuated, the reliably the transparent or semi-transparent body can be detected. The angle α can be increased in proportion to the transparency of the pages of the book 1, thereby to enhance the accuracy of detecting the turning of pages.

The angle α can be one defined with respect to anything other than the direction in which the book 1 is transported. For example, the angle α can be 0° in the case where the axis of the page-turning rollers 63 is inclined to the direction in which the book 1 is transported. In this case, the crest 1d of the bent page 1c moves upward in a different direction, and the same effect as in the above embodiment will result in. In other words, the path of the light beam can be inclined at a predetermined angle to a line which crosses at right angles to the crest 1d of the bent page 1c.

In the embodiment described above, the sensor 78 is a photosensor. The sensor 78 can be replaced by another type of a non-contact sensor, such as an ultrasonic-wave sensor, which can also detect how the pages of the book 1 are turned. Further, instead of the light-emitting element 78a, an optical sensor or an ultrasonic-wave sensor, which serves as a signal generating and receiving element may be used. In this case, instead of the light-receiving element 78b, a member for reflecting the light beam or the ultrasonic wave.

As may be understood from the above, the printing apparatus according to the present invention can perform a high-quality printing of characters or images in a book, even if printing is repeated several times in the same region of any page, and can print data on the entire surface of any pages of a book, without damaging the book.

The present invention is not limited to the embodiment described above. Various changes and modifications can be made within the scope of the present invention defined by the appended claims.

For instance, in the above embodiment, a tension is applied on a selected page of the book, other than the print page. However, a tension may be directly applied on the print page.

Either chucking member 82 of the chucking mechanism 80 can be replaced by the modified one shown in Fig. 15. The modified chucking member 82 comprises an L-shaped support plate 84. The support plate 84 is fastened to the platen-shaft 57 and is rotated when the shaft 57 rotates. The support plate 84 has an end portion extending over the circumference of the platen roller 56. A chucking arm 85 is rotatably connected to the end portion of the support plate 84 by an axle 106. A tension

spring 89 is stretched between pins 107 and 108 protruding from the arm 85 and the support plate 84, respectively. Due to the force of the spring 89, the arm 85 is pressed onto the circumference of the platen roller 56. The pin 107 is located forward of the line connecting the pin 108 and the axle 106, with respect to the direction K. The arm 85 is rotated by a drive unit (not shown) away from the platen roller 56, so that the fore-edge portion of the print page 1c may be inserted into the gap between the arm 85 and the circumference of the roller 56.

The force with which the arm 85 presses the fore-edge portion of the page 1c has a vector J which extends opposite to the direction K in which the print page 1c is transported. Hence, when a tension is applied on the print page 1c in the direction opposite to the direction K, either chucking arm 85 is rotated to press the fore-edge portion of the page 1c firmly onto the circumference of the platen roller 56, reliably preventing the print page 1c from slipping out of the chucking arms 85 throughout the printing process. In other words, the modified chucking arms 85 (Fig. 15) can reliably hold the print page 1c at a predetermined position during the printing process, ensuring high-quality printing.

25 Claims

1. An apparatus for printing data on any specified page of a book formed of a plurality of pages fastened together at a seam, said printing apparatus comprising:

means (38) for transporting the book to a predetermined position, while keeping a selected page (1a) of the book opened and located substantially parallel to the other pages including the specified page (1c) on which to print data;

means for positioning and holding the specified page (1c); and

means (96) for printing data on the specified page (1c);

characterized by further comprising:

page-turning means (62) for turning the specified page (1c) from the other pages of the book (1) transported by the transporting means; and

tension-applying means for pulling the selected page (1a) of the book (1), other than said specified page (1c) positioned and held by said positioning/holding means, so as to apply a tension on said specified page through the seam (1b) of the book.

2. An apparatus according to claim 1, characterized in that said tension-applying means has a first and a second clamping member (40b, 41b) for clamping the selected page (1a), and means for applying a force to at least one of the clamping members in a direction for applying a tension on the selected page.
3. An apparatus according to claim 2, characterized in that said at least one of said clamping members

(40b,41b) comprises a rotatable member (40b), and said tension-applying means has means (38) for rotating the rotatable member in a specific direction for applying a tension on the selected page (1a).

4. An apparatus according to claim 3, characterized in that said tension-applying means has pressure-adjusting means (46) for adjusting the pressure with which said first and second clamping members (40b,41b) clamp the selected page (1a), such that said rotatable member (40b) slides on the selected page to apply a sliding frictional force to the selected page.
5. An apparatus according to claim 1, characterized in that said tension-applying means has means for generating a sliding friction associated with the selected page (1a) so as to apply the tension to the selected page.
6. An apparatus according to claim 1, characterized in that said tension-applying means includes a member (40b) contacting the selected page, and means (46) for adjusting the contact pressure of the member with respect to the selected page (1a) so as to change the tension applied to the selected page.
7. An apparatus according to claim 1, characterized in that said positioning/holding means comprises a support member (56) for supporting the specified page (1c), and chucking means (80) for chucking the specified page (1c) onto the support member, and said printing means (96) has a print head (97b) opposing said support member, with the specified page interposed between said support member and said print head.
8. An apparatus according to claim 7, characterized in that said support member (56) is formed in a cylindrical shape and has an axis extending substantially parallel to the seam (1b) of the book (1), and by further comprising means (58) for rotating said support member such that the specified page (1c) placed on the support member is wrapped around the circumference of the support member.
9. An apparatus according to claim 7, characterized in that ~~the circumferential surface of said support member (56) is cut away to form a flat surface (56a)~~ which extends along the axis of the support member and is designed to position the specified page (1c) in such a way that the selected page (1a) opposes the other pages and is inclined at a predetermined angle to the other pages, when almost the whole specified page is wrapped around the support member.
10. An apparatus according to claim 1, characterized in that said page-turning means (62) has a page-turn-

ing member (63) for turning the specified page (1c) from the other pages, while sliding on the specified page and applying a frictional force thereto.

11. An apparatus according to claim 10, characterized in that said page-turning means (62) has a guide portion (66a) located between said support member (56) and said page-turning member (63), for guiding the fore-edge portion of the specified page (1c) turned from the other pages onto the support member.
12. An apparatus according to claim 11, characterized in that said page-turning means (62) further has means (66) supporting said page-turning member (63), such that said page-turning member is spaced apart from said support member (56) for a predetermined distance and is movable toward and away from the specified page (1c).
13. An apparatus according to claim 12, characterized in that said page-turning member (63) is a roller rotatably supported by said supporting means (66), and said page-turning means (62) has means for rotating the roller.
14. An apparatus according to claim 10, characterized in that said page-turning means (62) comprises:
 - drive means for driving said page-turning member (63) such that the page-turning member applies a frictional force on the specified page (1c), from the fore-edge portion thereof toward the seam (1b) of the book (1), thereby to bend the specified page upwards from the other pages, the bent specified page having a crest (1d) which extends substantially parallel to the seam of the book; and
 - means (78) for detecting the crest of the bent specified page to determine that the specified page is being turned.
15. An apparatus according to claim 14, characterized in that said detecting means (78) has a signal-generating section (78a) for generating a signal in a direction inclined at a predetermined angle to the crest (1d) of the bent specified page (1c), and a signal-receiving section (78b) for receiving the signal generated from the signal-generating section, said signal-receiving section opposing the signal-generating section with the, other pages interposed between said signal-generating section and said signal-receiving section, and designed to output a signal when the crest of the bent specified page interrupts the signal generated from said signal-generating section.
16. An apparatus according to claim 15, characterized in that said signal-generating section (78a) is a light-emitting section for emitting a light beam.

17. An apparatus according to claim 7, characterized in that said book-transporting means (38) comprises:
 guide means (16) having an upper guide (22a, 22b) and a lower guide (20a, 20b, 20c) opposing the upper guide, for defining a book-transporting path (23) between the upper and lower guides;
 a plurality of lower rollers (41a, 41b, 41c) arranged along the book-transporting path;
 a plurality of upper rollers (40a, 40b, 40c) arranged along the book-transporting path and contacting said lower rollers, the contacting portions of said lower rollers and upper rollers being located in the book-transporting path; and
 roller-driving means for driving either said lower rollers or said upper rollers, such that the book is transported through said book-transporting path, while being clamped between said lower rollers on the one hand, and said upper rollers on the other hand.
18. An apparatus according to claim 17, characterized in that said lower guide (20a, 20b, 20c) has a movable lower guide section (20b) located below the other pages when the book (1) is transported to said predetermined position, said movable lower guide section being movable between an upper position where the lower guide section defines said book-transporting path, and a lower position where the lower guide section is remote from said book-transporting path; and said guide means (16) has lower guide driving means (24) for holding said lower guide section at the upper position while said page-turning means (62) turns the specified page (1c), and for guiding said lower guide section to the lower position after said page-turning means turns the specified page.
19. An apparatus according to claim 17, characterized in that said upper guide (22a, 22b) has a movable upper guide section (22b) movable between a forward position where the upper guide section is located above the other pages of the book (1) transported to said predetermined position, and a rearward position where the upper guide section uncover the other pages, and said guide means (16) has upper guide driving means (29) for guiding said upper guide section to the rearward position while said page turning means (62) turns the specified page.
20. An apparatus according to claim 17, characterized in that said upper rollers (40a, 40b, 40c) and said lower rollers (41a, 41b, 41c) include an upper clamping roller (40b) and a lower clamping roller (41b) which are arranged such that they clamp the selected page (1a) of the book (1) transported to said predetermined position; and said tension-applying means includes a roller support member (43) supporting said upper clamping roller such that

said upper clamping roller is movable into contact with said lower clamping roller and away therefrom, means (45) for biasing said upper clamping roller toward said lower clamping roller, and pressure-adjusting means (46) for adjusting the pressure which said biasing means applies to said upper clamping roller, such that said upper clamping roller contacts said lower clamping roller with a predetermined pressure when the book is transported or when the specified page is turned, and also such that said upper clamping roller contacts said lower clamping roller with a pressure lower than the predetermined pressure and slip on said selected page to apply a tension on the selected page while said printing means (96) print data on the specified page (1c).

21. An apparatus according to claim 1, characterized in that said positioning/holding means comprises a support member (56) for supporting the specified page, and chucking means (80) for cooperating with the support member to chuck the specified page, and said chucking means has a chucking member (82) movable between a chucking position where the chucking member contacts said support member and a waiting position where the chucking member is remote from said support member, and means (89) for pressing said chucking member onto said support member with a force having a vector component extending in the same direction said tension acts on the specified page, when said chucking member moves to the chucking position.
22. An apparatus according to claim 21, characterized in that said chucking means (80) has means for detecting whether or not the specified page (1c) is clamped between said chucking member (82) and said support member (56), in accordance with the position of said chucking member.
23. An apparatus according to claim 22, characterized in that said detecting means includes a detecting member (95a) attached to said chucking member (82) to be rotated together with the chucking member, and a sensor (95b) for sensing the distance between the position which said detecting member takes when said chucking member is at the chucking position while the specified page (1c) is not clamped between the support member (56) and the chucking member and the position said detecting member takes when said chucking member clamps the specified page at the chucking position.
24. An apparatus according to claim 22, characterized in that said detecting means has a pressure sensor (102) provided on that portion of the chucking member (82) which opposes said support member (56) of said positioning/holding means.

Patentansprüche

1. Vorrichtung zum Drucken von Daten auf einer gegebenen bezeichneten Seite eines Buchs, bestehend aus einer Vielzahl von an einem Falzabschnitt (seam) fest miteinander verbundenen bzw. gebundenen Seiten, welche Druckvorrichtung umfaßt:
 - eine Einheit (38) zum Transportieren des Buchs zu einer vorbestimmten Position, während eine gewählte Seite (1a) des Buchs geöffnet (aufgeschlagen) und im wesentlichen parallel zu den anderen Seiten, einschließlich der bezeichneten Seite (1c), auf welcher Daten ausgedruckt werden sollen, angeordnet gehalten wird,
 - eine Einheit zum Positionieren und Halten der bezeichneten Seite (1c) und
 - eine Einheit (96) zum Drucken von Daten auf der bezeichneten Seite (1c),
 - ferner gekennzeichnet durch
 - eine seitenwendeeinheit (62) zum Wenden oder Umschlagen der bezeichneten Seite (1c) gegenüber den anderen Seiten des durch die Transporteinheit transportierten Buchs (1) und
 - eine Zugspannungsanlegeeinheit zum Ziehen der gewählten Seite (1a) des Buchs (1), die von der bezeichneten, durch die Positionier/Halteeinheit positionierten und gehaltenen Seite (1c) verschieden ist, um die bezeichnete Seite über den Falzabschnitt (1b) des Buchs mit einer Zugspannung zu beaufschlagen.
2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Zugspannungsanlegeeinheit ein erstes und ein zweites Klemmelement (40b, 41b) zum Verklemmen der gewählten Seite (1a) und Mittel zum Ausüben einer Kraft auf mindestens eines der Klemmelemente in einer Richtung zum Beaufschlagen der gewählten Seite mit einer Zugspannung aufweist.
3. Vorrichtung nach Anspruch 2, dadurch gekennzeichnet, daß das mindestens eine Klemmelement (40b, 41b) ein drehbares Element (40b) umfaßt und die Zugspannungsanlegeeinheit Mittel (38) zum Drehen des drehbaren Elements in einer bestimmten Richtung zum Beaufschlagen der gewählten Seite (1a) mit einer Zugspannung aufweist.
4. Vorrichtung nach Anspruch 3, dadurch gekennzeichnet, daß die Zugspannungsanlegeeinheit eine Druckeinstelleinheit (46) zum Einstellen des Drucks, mit dem die ersten und zweiten Klemmelemente (40b, 41b) die gewählte Seite (1a) verklemmen, aufweist, derart, daß das drehbare Element (40b) auf der gewählten Seite gleitet bzw. rutscht und eine Gleitreibungskraft auf die gewählte Seite ausübt.
5. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Zugspannungsanlegeeinheit Mittel zum Erzeugen einer Gleitreibung in bezug auf (associated with) die gewählte Seite (1a), um die gewählte Seite mit der Zugspannung zu beaufschlagen, aufweist.
6. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Zugspannungsanlegeeinheit ein mit der gewählten Seite in Berührung stehendes Element (40b) und eine Einheit (46) zum Einstellen des Berührungsdrucks des Elements gegenüber der gewählten Seite (1a) zwecks Änderung der die gewählte Seite beaufschlagenden Zugspannung aufweist.
7. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Positionier/Halteeinheit ein Tragelement (56) zum Tragen oder Abstützen der bezeichneten Seite (1c) und eine (Ver-)Spanneinheit (80) zum Verspannen der bezeichneten Seite (1c) auf dem Tragelement umfaßt und die Druckeinheit (96) einen dem Tragelement mit zwischen Tragelement und Druckkopf eingefügter bezeichneter Seite gegenüberstehenden Druckkopf (97b) aufweist.
8. Vorrichtung nach Anspruch 7, dadurch gekennzeichnet, daß das Tragelement (56) zylindrisch geformt ist und eine im wesentlichen parallel zum Falzabschnitt (seam) (1b) des Buchs (1) verlaufende Achse aufweist, und ferner umfassend eine Einheit (58) zum Drehen des Tragelements in der Weise, daß die auf dem Tragelement platzierte bezeichnete Seite (1c) um den Umfang des Tragelements herumgewickelt wird.
9. Vorrichtung nach Anspruch 7, dadurch gekennzeichnet, daß die Umfangsfläche des Tragelements (56) unter Bildung einer Planfläche (56a) weggeschnitten bzw. ausgespart ist, welche Planfläche längs der Achse des Tragelements verläuft und ausgelegt ist zum Positionieren der bezeichneten Seite (1c) in der Weise, daß die gewählte Seite (1a) den anderen Seiten gegenüberliegt und unter einem vorbestimmten Winkel zu den anderen Seiten geneigt ist, wenn nahezu die gesamte bezeichnete Seite um das Tragelement herumgewickelt ist.
10. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Seitenwendeeinheit (62) ein Seitenwendeelement (63) zum Wenden oder Umschlagen der bezeichneten Seite (1c) gegenüber den anderen Seiten, während es auf der bezeichneten Seite gleitet bzw. rutscht und auf diese eine Reibungskraft ausübt, aufweist.
11. Vorrichtung nach Anspruch 10, dadurch gekennzeichnet, daß Seitenwendeeinheit (62) ein zwischen dem Tragelement (56) und dem Seitenwendeelement (63) angeordnetes Führungsteil (66a) zum

Führen des Vorderkantenabschnitts der von den anderen Seiten (hinweg) gewendeten bzw. umgeschlagenen bezeichneten Seite (1c) auf das Tragelement aufweist.

12. Vorrichtung nach Anspruch 11, dadurch gekennzeichnet, daß die Seitenwendeinheit (62) ferner eine Einheit (66) zum Lagern des Seitenwendeelements (63) in der Weise aufweist, daß das Seitenwendeelement in einem vorbestimmten Abstand vom Tragelement (56) angeordnet und auf die bezeichnete Seite (1c) zu und von ihr hinweg bewegbar ist.
13. Vorrichtung nach Anspruch 12, dadurch gekennzeichnet, daß das Seitenwendeelement (63) eine durch die Lagereinheit (66) drehbar gelagerte Rolle ist und die Seitenwendeinheit (62) Mittel zum Drehen der Rolle aufweist.
14. Vorrichtung nach Anspruch 10, dadurch gekennzeichnet, daß seitenwendeinheit (62) umfaßt:
Antriebsmittel zum Antreiben des Seitenwendeelements (63) in der Weise, daß letzteres eine Reibungskraft auf die bezeichnete Seite (1c), von ihrem Vorderkantenabschnitt aus in Richtung auf den Falzabschnitt (seam) (1b) des Buchs (1), ausübt, um damit die bezeichnete Seite von den bzw. gegenüber den anderen Seiten aufwärts zu wölben oder durchzubiegen, wobei die durchgebogene bezeichnete Seite einen im wesentlichen parallel zum Falzabschnitt des Buchs verlaufenden Scheitelpunkt (1d) aufweist, und
eine Einheit (78) zum Detektieren des Scheitelpunkts der durchgebogenen bezeichneten Seite zwecks Bestimmung, daß die bezeichnete Stelle gewendet bzw. umgeschlagen ist oder wird.
15. Vorrichtung nach Anspruch 14, dadurch gekennzeichnet, daß die Detektiereinheit (78) eine in einer unter einem vorbestimmten Winkel zum Scheitelpunkt (1d) der durchgebogenen bezeichneten Seite (1c) schräggestellten Richtung angeordnete Signalerzeugungssektion (78a) zum Erzeugen eines Signals und eine Signalempfangssektion (78b) zum Empfangen des durch die Signalerzeugungssektion erzeugten Signals aufweist, wobei die Signalempfangssektion der Signalerzeugungssektion gegenübersteht, während die anderen Seiten zwischen die Signalerzeugungssektion und die Signalempfangssektion eingefügt sind, und ausgelegt ist zum Ausgeben eines Signals, wenn der Scheitelpunkt der durchgebogenen bezeichneten Seite das von der Signalerzeugungssektion erzeugte Signal unterbricht.
16. Vorrichtung nach Anspruch 15, dadurch gekennzeichnet, daß die Signalerzeugungssektion (78a)

eine lichtemittierende Sektion zum Emittieren eines Lichtstrahls ist.

17. Vorrichtung nach Anspruch 7, dadurch gekennzeichnet, daß die Buchtransporteinheit (38) umfaßt:
eine Führungseinheit (16) mit einer oberen Führung (22a, 22b) und einer der oberen Führung gegenüberstehenden unteren Führung (20a, 20b, 20c) zur Festlegung einer Buchtransportstrecke (23) zwischen den oberen und unteren Führungen, eine Anzahl von längs der Buchtransportstrecke angeordneten unteren Rollen (41a, 41b, 41c),
eine Anzahl von längs der Buchtransportstrecke angeordneten und mit den unteren Rollen in Berührung stehenden oberen Rollen (40a, 40b, 40c), wobei die Berührungsabschnitte der unteren und der oberen Rollen in der Buchtransportstrecke angeordnet sind, und
eine Rollenantriebseinheit zum Antreiben entweder (bzw. jeder) der unteren Rollen oder der oberen Rollen, derart, daß das Buch auf der Buchtransportstrecke transportiert wird, während es zwischen den unteren Rollen einerseits und den oberen Rollen andererseits verklemmt ist.
18. Vorrichtung nach Anspruch 17, dadurch gekennzeichnet, daß die untere Führung (20a, 20b, 20c) eine bewegbare untere Führungssektion (20b) aufweist, die unter den anderen Seiten angeordnet ist, wenn das Buch (1) zu der vorbestimmten Position transportiert wird oder ist, die bewegbare untere Führungssektion zwischen einer oberen Stellung, in welcher die untere Führungssektion die Buchtransportstrecke festlegt, und einer unteren Stellung bewegbar ist, in welcher die untere Führungssektion von der Buchtransportstrecke entfernt bzw. beabstandet ist, und die Führungseinheit (16) eine untere Führungsantriebseinheit (24) zum Halten der unteren Führungssektion in der oberen Stellung, während die Seitenwendeinheit (62) die bezeichnete Seite (1c) wendet bzw. umschlägt, und zum Führen der unteren Führungssektion in die untere Stellung, nachdem die Seitenwendeinheit die bezeichnete Seite gewendet bzw. umgeschlagen hat, aufweist.
19. Vorrichtung nach Anspruch 17, dadurch gekennzeichnet, daß die obere Führung (22a, 22b) eine bewegbare obere Führungssektion (22b) aufweist, die zwischen einer vorderen Stellung, in welcher die obere Führungssektion über den anderen Seiten des zur vorbestimmten Position transportierten Buchs (1) liegt, und einer hinteren Stellung bewegbar ist, in welcher die obere Führungssektion die anderen Seiten aufdeckt bzw. freilegt, und die Führungseinheit (16) eine obere Führungsantriebseinheit (29) zum Führen der oberen Führungssektion in die hintere Stellung, während die Seitenwende-

einheit (62) die bezeichnete Seite wendet oder umschlägt, aufweist.

20. Vorrichtung nach Anspruch 17, dadurch gekennzeichnet, daß die oberen Rollen (40a, 40b, 40c) und die unteren Rollen (41a, 41b, 41c) eine obere Klemmrolle (40b) und eine untere Klemmrolle (41b) aufweisen, die so angeordnet sind, daß sie die gewählte Seite (1a) des zur vorbestimmten Position transportierten Buchs (1) verklemmen, und die Zugspannungsanlegeeinheit ein Rollenlagerelement (43), welches die obere Klemmrolle so lagert oder trägt, daß die obere Klemmrolle in Berührung mit der unteren Klemmrolle und von dieser hinweg bewegbar ist, ein Mittel (45) zum Vorbelasten der oberen Klemmrolle gegen die untere Klemmrolle und eine Druckeinstelleinheit (46) zum Einstellen des durch das Vorbelastungsmittel auf die obere Klemmrolle ausgeübten Drucks aufweist, derart, daß die obere Klemmrolle die untere Klemmrolle mit einem vorbestimmten Druck kontaktiert, wenn das Buch transportiert oder die bezeichnete Seite gewendet bzw. umgeschlagen wird, und auch derart, daß die obere Klemmrolle die untere Klemmrolle mit einem geringeren Druck als dem vorbestimmten Druck kontaktiert und auf der gewählten Seite (durch)rutscht, um damit eine Zugspannung auf die gewählte Seite auszuüben, während die Druckeinheit (96) Daten auf die bezeichnete Seite (1c) aufdruckt.

21. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Positionier/Halteeinheit ein Tragelement (56) zum Tragen oder Abstützen der bezeichneten Seite und eine mit dem Tragelement zusammenwirkende Spanneinheit (80) zum Verspannen (oder Einspannen) der bezeichneten Seite aufweist und die Spanneinheit ein Spannelement bzw. Spannstück (82), das zwischen einer Verspannstellung, in welcher es mit dem Tragelement in Berührung steht, und einer Wartestellung bewegbar ist, in welcher das Spannelement vom Tragelement entfernt oder beabstandet ist, und ein Mittel (89) zum Anpressen des Spannelements (bzw. Spannstücks) an das Tragelement mit einer Kraft mit einer Vektorkomponente, die in der gleichen Richtung, in welcher die Zugspannung auf die bezeichnete Seite einwirkt, verläuft, wenn sich das Spannelement in die Verspannstellung bewegt, aufweist.

22. Vorrichtung nach Anspruch 21, dadurch gekennzeichnet, daß die Spanneinheit (80) ein Mittel zum Detektieren, ob die bezeichnete Seite (1c) zwischen dem Spannelement (82) und dem Tragelement (56) verklemmt (bzw. verspannt) ist oder nicht, nach Maßgabe der Stellung des Spannelements aufweist.

23. Vorrichtung nach Anspruch 22, dadurch gekennzeichnet, daß das Detektiermittel ein am Spannelement (82) für Mitdrehung mit diesem angebrachtes Detektiermittel (95a) und einen Sensor (95b) zum Messen oder Bestimmen des Abstands zwischen der Stellung, die das Detektierelement einnimmt, wenn sich das Spannelement in der Verspannstellung befindet, während die bezeichnete Seite (1c) nicht zwischen dem Tragelement (56) und dem Spannelement verklemmt (bzw. verspannt) ist, und der Stellung, welche das Detektierelement einnimmt, wenn das Spannelement die bezeichnete Seite in der Verspannstellung verklemmt (bzw. verspannt), aufweist.

24. Vorrichtung nach Anspruch 22, dadurch gekennzeichnet, daß das Detektiermittel einen Drucksensor (102) aufweist, der an dem Teil des Spannelements (82) vorgesehen ist, welcher dem Tragelement (56) der Positionier/Halteeinheit gegenübersteht.

Revendications

1. Appareil pour imprimer des données sur une page spécifiée quelconque d'un livret formé d'une pluralité de pages fixées ensemble au niveau d'une reliure, ledit appareil d'impression comprenant :

- des moyens (38) pour transporter le livret jusqu'à une position prédéterminée, tout en maintenant une page choisie (1a) du livret ouverte et placée sensiblement parallèlement aux autres pages, y compris la page spécifiée (1c) sur laquelle on doit imprimer des données ;
- des moyens pour positionner et maintenir la page spécifiée (1c) ; et
- des moyens (96) pour imprimer des données sur la page spécifiée (1c) ; caractérisé en ce qu'il comprend en outre :
- des moyens de tournage de page (62) pour tourner la page spécifiée (1c) depuis les autres pages du livret (1) transporté par les moyens de transport ; et
- des moyens d'application de tension pour tirer la page choisie (1a) du livret (1), autre que ladite page spécifiée (1c) positionnée et maintenue par lesdits moyens de positionnement et de maintien, de manière à appliquer une tension sur ladite page spécifiée par l'intermédiaire de la reliure (1b) du livret.

2. Appareil selon la revendication 1, caractérisé en ce que lesdits moyens d'application de tension comportent un premier et un second élément de serrage (40b, 41b) pour serrer la page choisie (1a), et des moyens pour appliquer une force à l'un au moins des éléments de serrage dans une direction pour appliquer une tension sur la page choisie.

3. Appareil selon la revendication 2, caractérisé en ce que ledit au moins un élément de serrage (40b, 41b) comprend un élément rotatif (40b), et lesdits moyens d'application de tension comportent des moyens (38) pour faire tourner l'élément rotatif dans une direction spécifique pour appliquer une tension sur la page choisie (1a). 5
4. Appareil selon la revendication 3, caractérisé en ce que les moyens d'application de tension comprennent des moyens de réglage de pression (46) pour régler la pression avec laquelle lesdits premier et second éléments de serrage (40b, 41b) serrent la page choisie (1a), de telle sorte que ledit élément rotatif (40b) coulisse sur la page choisie pour appliquer une force de friction de glissement à la page choisie. 10 15
5. Appareil selon la revendication 1, caractérisé en ce que lesdits moyens d'application de tension comportent des moyens pour produire une friction de glissement, associés à la page choisie (1a) de manière à appliquer la tension à la page choisie (1a). 20
6. Appareil selon la revendication 1, caractérisé en ce que lesdits moyens d'application de tension comportent un élément (40b) en contact avec la page choisie, et des moyens (46) pour régler la pression de contact de l'élément par rapport à la page choisie (1a) de manière à changer la tension appliquée à la page choisie. 25 30
7. Appareil selon la revendication 1, caractérisé en ce que lesdits moyens de positionnement et de maintien comprennent un élément de support (56) pour supporter la page spécifiée (1c), et des organes de prise (80) pour serrer la page spécifiée (1c) sur l'élément de support, et lesdits moyens d'impression (96) comportent une tête d'impression (97b) à l'opposé dudit élément de support, la page spécifiée étant interposée entre ledit élément de support et ladite tête d'impression. 35 40
8. Appareil selon la revendication 7, caractérisé en ce que ledit élément de support (56) est réalisé avec une forme cylindrique et comporte un axe qui s'étend sensiblement parallèlement à la reliure (1b) du livret (1), et en ce qu'il comprend en outre des moyens (58) pour faire tourner ledit élément de support de façon que la page spécifiée (1c) placée sur l'élément de support est enroulée autour de la circonférence de l'élément de support. 45 50
9. Appareil selon la revendication 7, caractérisé en ce que la surface circonférentielle dudit élément de support (56) est découpée pour former une surface plane (56a) qui s'étend le long de l'axe de l'élément de support et qui est conçue pour positionner la page spécifiée (1c) d'une telle manière que la page

choisie (1a) est opposée aux autres pages, et qu'elle est inclinée sous un angle prédéterminé par rapport aux autres pages, lorsque pratiquement la totalité de la page spécifiée est enroulée autour de l'élément de support.

10. Appareil selon la revendication 1, caractérisé en ce que lesdits moyens de tournage de page (62) comportent un élément de tournage de page (63) pour tourner la page spécifiée (1c) depuis les autres pages, tout en glissant sur la page spécifiée et en lui appliquant une force de friction.
11. Appareil selon la revendication 10, caractérisé en ce que lesdits moyens de tournage de page (62) comportent une partie de guidage (66a) située entre ledit élément de support (56) et ledit élément de tournage de page (63), pour guider la partie de bordure avant de la page spécifiée (1c) tournée depuis les autres pages sur l'élément de support.
12. Appareil selon la revendication 11, caractérisé en ce que lesdits moyens de tournage de page (62) comportent en outre des moyens (66) qui supportent ledit élément de tournage de page (63), de sorte que ledit élément de tournage de page est espacé depuis ledit élément de support (56) d'une distance prédéterminée, et mobile en direction et en éloignement de la page spécifiée (1c).
13. Appareil selon la revendication 12, caractérisé en ce que ledit élément de tournage de page (63) est un galet supporté en rotation par lesdits moyens de support (66), et en ce que lesdits moyens de tournage de page (62) comportent des moyens pour faire tourner le galet.
14. Appareil selon la revendication 10, caractérisé en ce que lesdits moyens de tournage de page (62) comprennent :
 - des moyens d'entraînement pour entraîner ledit élément de tournage de page (63) de façon que l'élément de tournage de page applique une force de friction sur la page spécifiée (1c), depuis la partie de bordure avant de celle-ci en direction de la reliure (1b) du livret (1), pour recourber ainsi la page spécifiée vers le haut depuis les autres pages, la page spécifiée recourbée ayant un sommet (1d) qui s'étend sensiblement parallèlement à la reliure du livret ; et
 - des moyens (78) pour détecter le sommet de la page incurvée spécifiée pour déterminer que la page spécifiée est tournée.
15. Appareil selon la revendication 14, caractérisé en ce que lesdits moyens de détection (78) comportent une unité de production de signaux (78a) pour pro-

duire un signal dans une direction inclinée sous un angle prédéterminé par rapport au sommet (1d) de la page spécifiée incurvée (1c), et une unité de réception de signaux (78b) pour recevoir le signal produit depuis l'unité de production de signaux, ladite unité de réception de signaux étant opposée à l'unité de production de signaux, tandis que les autres pages sont interposées entre l'unité de production de signaux et l'unité de réception de signaux, et sont conçus pour délivrer un signal lorsque le sommet de la page spécifiée incurvée interrompt le signal produit depuis ladite unité de production de signaux.

16. Appareil selon la revendication 15, caractérisé en ce que ladite unité de production de signaux (78a) est une unité d'émission de lumière pour émettre un faisceau lumineux.

17. Appareil selon la revendication soit, caractérisé en ce que lesdits moyens de transport (38) comprennent :

- des moyens de guidage (16) ayant un guide supérieur (22a, 22b) et un guide inférieur (20a, 20b, 20c) opposé au guide supérieur, pour définir un trajet de transport de livret (23) entre les guides supérieur et inférieur ;
- une pluralité de galets inférieurs (41a, 41b, 41c) agencés le long du trajet de transport ;
- une pluralité de galets supérieurs (40a, 40b, 40c) agencés le long du trajet de transport et en contact avec lesdits galets inférieurs, les parties en contact desdits galets inférieurs et desdits galets supérieurs étant situées dans le trajet de transport ; et
- des moyens d'entraînement de galets pour entraîner soit lesdits galets inférieurs soit lesdits galets supérieurs, de sorte que le livret est transporté le long dudit trajet de transport, tandis qu'il est serré entre lesdits galets inférieurs d'une part et lesdits galets supérieurs d'autre part.

18. Appareil selon la revendication 17, caractérisé en ce que ledit guide inférieur (20a, 20b, 20c) comporte un tronçon de guidage inférieur mobile (20b) situé au-dessous des autres pages lorsque le livret (1) est transporté jusqu'à ladite position prédéterminée, ledit tronçon de guidage inférieur mobile étant mobile entre une position supérieure dans laquelle le tronçon de guidage inférieur définit ledit trajet de transport, et une position inférieure dans laquelle le tronçon de guidage inférieur est éloigné dudit trajet de transport ; et en ce que lesdits moyens de guidage (16) comportent des moyens d'entraînement de guide inférieur (24) pour maintenir ledit tronçon de guidage inférieur à ladite position supérieure tandis que lesdits moyens de tournage de page (62)

font tourner la page spécifiée (1c), et pour guider ledit tronçon de guidage inférieur vers la position inférieure après que lesdits moyens de tournage de page aient tourné la page spécifiée.

19. Appareil selon la revendication 17, caractérisé en ce que ledit guide supérieur (22a, 22b) comporte un tronçon de guidage supérieur mobile (22b) mobile entre une position avancée dans laquelle le tronçon de guidage supérieur est situé au-dessus des autres pages du livret (1) transporté jusqu'à ladite position prédéterminée, et une position reculée dans laquelle le tronçon de guidage supérieur découvre les autres pages, et en ce que lesdits moyens de guidage (16) comportent des moyens d'entraînement de guide supérieur (29) pour guider ledit tronçon de guidage supérieur vers la position reculée tandis que lesdits moyens de tournage de page (62) tournent la page spécifiée.

20. Appareil selon la revendication 17, caractérisé en ce que lesdits galets supérieurs (40a, 40b, 40c) et lesdites galets inférieurs (41a, 41b, 41c) comprennent un galet pinceur supérieur (40b) et un galet pinceur inférieur (41b) qui sont agencés de telle manière qu'ils serrent la page choisie (1a) du livret (1) transporté jusqu'à ladite position prédéterminée ; et en ce que lesdits moyens d'application de tension comprennent un élément de support de galet (43) qui supporte ledit galet pinceur supérieur de telle manière que ledit galet pinceur supérieur est mobile en contact avec ledit galet pinceur inférieur et en éloignement de celui-ci, des moyens (45) pour solliciter ledit galet pinceur supérieur en direction dudit galet pinceur inférieur, et des moyens de réglage de pression (46) pour régler la pression que lesdits moyens de sollicitation appliquent audit galet pinceur supérieur, de telle façon que ledit galet pinceur supérieur vient en contact avec ledit galet pinceur inférieur avec une pression prédéterminée lorsque le livret est transporté ou bien lorsque la page spécifiée est tournée, et également de telle façon que ledit galet pinceur supérieur vient en contact avec ledit galet pinceur inférieur avec une pression inférieure à la pression prédéterminée et glisse sur ladite page choisie pour appliquer une tension à la page choisie tandis que lesdits moyens d'impression (96) impriment des données sur la page spécifiée (1c).

21. Appareil selon la revendication 1, caractérisé en ce que lesdits moyens de positionnement et de maintien comprennent un élément de support (56) pour supporter la page spécifiée, et des moyens de prise (80) pour coopérer avec l'élément de support pour serrer la page spécifiée, et lesdits moyens de prise comprennent un élément de prise (82) mobile entre une position de serrage dans laquelle l'élément de prise vient en contact avec ledit élément de support,

et une position d'attente dans laquelle l'élément de prise est éloigné dudit élément de support, et des moyens (89) pour presser ledit élément de prise sur ledit élément de support avec une force qui présente une composante vectorielle qui s'étend dans la même direction que l'action de la tension sur la page spécifiée, lorsque ledit élément de prise se déplace jusqu'à la position de serrage.

22. Appareil selon la prolifération 21, caractérisé en ce que lesdits moyens de prise (80) comportent des moyens pour détecter si la page spécifiée (1c) est serrée ou non entre ledit élément de prise (82) et ledit élément de support (56), selon la position dudit élément de prise.

23. Appareil selon la revendication 22, caractérisé en ce que lesdits moyens de détection comprennent un élément de détection (95a) attaché audit élément de prise (82) pour être mis en rotation ensemble avec l'élément de prise, et un capteur (95b) pour détecter la distance entre la position que ledit élément de détection occupe lorsque ledit élément de prise est dans la position de serrage tandis que la page spécifiée (1c) n'est pas serrée entre l'élément de support (56) et l'élément de prise, et la position que ledit élément de détection occupe lorsque ledit élément de prise serre la page spécifiée à la position de serrage.

24. Appareil selon la revendication 22, caractérisé en ce que lesdits moyens de détection comportent un capteur de pression (102) prévu sur la partie de l'élément de prise (82) qui est opposée audit élément de support (56) desdits moyens de positionnement et de maintien.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12



F I G. 13




FIG. 14




FIG. 15